

TRIPOD CHECKPOINT SERIES



SCR-TRP-SA

PRODUCT OVERVIEW

- Bi-directional drop-arm tripod turnstile.
- Passage can be controlled by remote push button.
- One passage at a time.
- LED direction guides with buzzer.
- Arm drop down in case of power failure or emergency.
- Automatic reset function.
- Auto locking upon passage access status (complete/incomplete).
- Adjustable preset time.
- Anti-collision, ant-reversal pass, and anti-trailing.
- Hydraulic buffer function for low noise operation.
- Lock/unlocks upon notification signal.
- Stable and robust enclosure.
- Integration with third party:
 - ✓ RFID access control system.
 - ✓ Card collector machine.

TECHNICAL SPECIFICATIONS

PHYSICAL PROPERTIES		SCR-TRP-SA
Case Dimensions (LxWxH) (mm)		1200*280*980
Standard Housing Material		Stainless steel
Tripod Hub Material		Casting Aluminum
Arm Length (mm)		500
Passage Width (mm)		550
Weight (kg)		75
ELECTRICAL PROPERTIES		
Motor Voltage (V)		24V AC
Communication Interface		RS485/RS232/RJ45
OPERATIONAL PROPERTIES		
System Operation		Semi-Automatic
Access Control		Manual / Remote
MTBF		5,000,000
Transit Speed (person/minute)		30-40
Open / Close Time (s)		0.6
ENVIRONMENTAL PROPERTIES		
Work Environment		Indoor or outdoor under shelter

